SAFETY DATA SHEET

1. Identification

Product number 1000000206

Product identifier 6.5 OZ SHOOT OUT LB 12PK

Revision date 03-24-2015

Company information QUALITY CHEMICAL COMPANY

1835 NE 144 STREET

NORTH MIAMI, FL 33181 United States

Company phone General Assistance 305-944-2837

Emergency telephone US 1-866-836-8855 Emergency telephone outside 1-952-852-4646

US

Version # 04

Supersedes date 01-28-2015
Recommended use Not available.
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Health hazardsNot classified.Environmental hazardsNot classified.OSHA defined hazardsNot classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	60 - 80
Propane		74-98-6	20 - 40
Ethyl Alcohol		64-17-5	2.5 - 10
Other components below reportable levels			0.01 - 0.1

^{#:} This substance has workplace exposure limit(s).

Product name: 6.5 OZ SHOOT OUT LB 12PK

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Move to fresh air. Get medical attention if symptoms persist. Inhalation

Skin contact Rinse skin with water/shower.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

Direct contact with eyes may cause temporary irritation.

present and easy to do.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

Most important

symptoms/effects, acute and

delayed

Provide general supportive measures and treat symptomatically.

Indication of immediate medical attention and special

treatment needed **General information**

Take off all contaminated clothing immediately.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Specific methods

General fire hazards

media

Water fog. Dry chemical powder.

None known.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle or store near an open flame, heat or other sources of ignition. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	•		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s). Explosion-proof general and local exhaust ventilation.

. . .

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If permissible levels are exceeded use

1000 ppm

NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateGas.FormAerosol.Colorclear colorless

Odor fruity

Odor threshold Not available.

pH Not applicable estimated

Melting point/freezing point Not available.

Initial boiling point and boiling

range

22.1 °F (-5.5 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Product name: 6.5 OZ SHOOT OUT LB 12PK

SDS US

Product #: 1000000206 Version #: 04 Revision date: 03-24-2015 Issue date: 08-11-2014

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.6 % estimated

Flammability limit - upper

(%)

12.8 % estimated

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

60 - 70 psig @ 70F estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

856.4 °F (458 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

0.57 estimated estimated Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point.

Incompatible materials Fluorine. Chlorine. Nitrates.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

Inhalation No adverse effects due to inhalation are expected. Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Product #: 1000000206 Version #: 04 Revision date: 03-24-2015 Issue date: 08-11-2014

Information on toxicological effects

Expected to be a low hazard for usual industrial or commercial handling by trained personnel. Acute toxicity

Product Species **Test Results**

6.5 OZ SHOOT OUT LB 12PK (CAS Mixture)

Acute Inhalation

LC50 Rat 489 mg/l/4h

Oral LD50

Rat

Test Results Components **Species**

Butane (CAS 106-97-8)

Acute Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

Product name: 6.5 OZ SHOOT OUT LB 12PK

SDS US

Components	Species	Test Results
		52 %, 120 Minutes
	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	1187 - 2769 mg/kg
		7800 ml/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
		-

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Possible reproductive hazard.

Specific target organ toxicity -

Respiratory or skin sensitization

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Ethyl Alcohol (CAS 64-17-5)		

/ Alcohol (CAS 04-17-3

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 7700 - 11200 mg/l, 48 hours

 Components **Species Test Results**

LC50 Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours Fish

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

2.89 -0.31 Ethyl Alcohol Propane 2.36

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN number**

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

^{*} Estimates for product may be based on additional component data not shown.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code

LTD QTY Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulationsOSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 08-11-2014

 Revision date
 03-24-2015

Version # 04

DisclaimerThe information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Alternate Trade Names

Product name: 6.5 OZ SHOOT OUT LB 12PK SDS US