

NON-SLIP FLOOR TREATMENT

DESCRIPTION

Slip Not is not a coating that can wear and that requires repeated re-application.

Slip Not is a fast-acting, water-based low odor treatment that transforms floors into a slip-resistant surface by increasing the coefficient of friction to ensure stability.

Slip Not microscopically etches the surface of the floor to help reduce the possibility of slipping and falling.

Slip Not is the best choice for treating slippery floors.

Where you have a slippery floor, you can treat it and make floors more slip resistant. Take action to make slippery floors safer!

USAGE

For use on quarry or ceramic tile floors, concrete, slate, terrazzo and others hard mineral surfaces. Also proven effective on bathtubs and showers. Designed exclusively for industrial use by trained professional maintenance personnel.

DIRECTIONS

NOTE: This product will microscopically etch the surface of the floor. This product will remove the shine from floors. DO NOT USE WITH CHLORINE-BASED PRODUCTS.

1 Gallon of *Slip No*t will cover approximately 1,500 - 2,000 sq. ft. depending upon porosity of surface. Ready to Use.

Slip Not was formulated to be a quick, easy to apply on non-coated slate, terrazzo, concrete & tile floors. Clean thoroughly to remove all dirt, grease and debris. Always test product in an inconspicuous area before applying. Apply at small areas using an applicator, mop or pressure sprayer (see Caution when using a sprayer). The floor is kept wet with the treatment, usually for 15 to 20 minutes, and then rinsed away with clean, cold water. Treating may be repeated until desired grip is obtained. Remove product by rinsing thoroughly and squeegee off excess of water. If no drains are available, use a wet-vac to remove Slip Not, then mop with fresh water. This simple process will increase the coefficient of friction and will typically be effective for many years with proper maintenance. The floor can be put back into use immediately. There is no cure time as with coatings.

PRODUCT SPECIFICATIONS

APPEARANCE Colorless, clear liquid

ODOR Mild **SPECIFIC GRAVITY at 77°F** 1.02 pH at 77 °F 4.7 WATER SOLUBILITY 100%

SHELF LIFE 2 Years in unopened container 55, 35, 15 Gallon drums **PACKAGING**

5 Gallon pails

Cases of 6/1 and 4/1 Gallon jugs

SAFETY INFORMATION

WARNING: USE IN OPEN, WELL VENTILATED AREAS. Use rubber gloves and safety goggles.

Caution: When using a pressure sprayer for application, avoid breathing the mist or getting the spray on yourself.

FIRST AID

EYE CONTACT: Flush with water for at least fifteen (15) minutes. Use a carbonated solution. Seek medical attention immediately.

SKIN CONTACT: Wash thoroughly with soap and water.

INGESTION: Seek medical attention immediately. Do not induce vomiting. Drink copious amounts of water.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. STORE IN A COOL, DRY PLACE.



Quality Chemical (305) 944-2837 • (888) 355-5540 • Fax (305) 944-6857 www.QualityChemical.com 1835 N.E. 144th Street, North Miami, Florida 33181