

Seal Remover

FAST ACTING
SOLVENT BLEND

REMOVES
PERMANENT TYPE FINISHES
FROM TERRAZZO, CONCRETE
STONE SURFACES

Product # 122

DESCRIPTION

A non-corrosive, non-butyl floor seal and finish remover, recommended for the removal of permanent type solvent-based sealers and coatings. This fast-acting floor finish remover dissolves multiple coats of finish without harsh alkalis. No neutralizing needed. No foam and free rinsing characteristics assure that no residue is left behind to interfere with subsequent finish applications.

BENEFITS

- * FAST ACTING, STRONG ACTION
- * REMOVES FINISHES COMPLETELY
- * INDUSTRIAL STRENGTH

USAGE

Recommended for industrial, commercial, institutional as well as household use.

DIRECTIONS

WEAR RUBBER GLOVES, SAFETY GLASSES, PROTECT SKIN AND EYES.

Apply a very thick coat of remover to surface with brush and let work at least for 10 minutes. Remove old finish with coarse steel wool or rags, and strong detergent and water solution. Numerous coats of old finish, or epoxy and urethane finishes, may require additional applications. A paint scraper may be helpful in removing extra heavy coats of old dissolved finish. Wood veneers should be washed off with mineral spirits -NOT WATER.

Completely wash off remover within 30 minutes, before it dries. *DO NOT USE ON ASPHALT, VINYL, RUBBER PLASTIC, FIBERGLASS-POLYESTER OR HOT SURFACES.*

PRODUCT SPECIFICATIONS

APPEARANCE	Amber viscous liquid
ODOR	Solvent like
FLASH POINT	>212°F
WEIGHT / Gallon @ 77°F	9.96 Lbs
WATER SOLUBILITY	Total
SHELF LIFE	1 Year in unopened container
PACKAGING	55 Gallon drums 5 Gallon pails Cases of 6/1 and 4/1 gallon jugs

SAFETY INFORMATION

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

DANGER: Contains Methylene Chloride, Xylene and Methanol. Harmful or fatal if swallowed. Vapors may be harmful. Skin and eye irritant. Flammable liquid. DOT Class 6.1, UN 1593.

FIRST AID

SKIN: Wash thoroughly with plenty of water. If irritation develops, seek medical attention. **EYES:** immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention immediately. **INGESTION:** Do not induce vomiting. Seek medical attention immediately. Keep away from heat, sparks and open flames. Contact with flames or hot surfaces may produce toxic gases. Avoid prolonged or repeated breathing of vapors or contact with skin and or eyes. Use with adequate ventilation. Close container after each use. Do not transfer contents to unlabeled bottles or other containers. STORE IN A COOL, DRY PLACE.

Quality  **Chemical**

1835 N.E. 144th Street, North Miami, Florida 33181
(305) 944-2837 • (888) 355-5540 • Fax (305) 944-6857
www.QualityChemical.com