



DESCRIPTION

MOISTURE DISPLACER demoisturizes and creates a waterproof film that dries out electrical equipment. Inhibits corrosion and prevents electrical discharge. Protects and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.

BENEFITS

- * **NON-FLAMMABLE**
- * **CONTAINS NO CHLORINATED SOLVENTS**
- * **DISPLACES WATER AND LUBRICATES**
- * **39,000 VOLT DIELECTRIC STRENGTH**

USAGE

Recommended for industrial, commercial, institutional as well as household use.

DIRECTIONS

TO DISPLACE MOISTURE: Spray electrical equipment until thoroughly saturated. Allow to penetrate before attempting to restart, then re-apply to protect surface. **TO LOOSEN FROZEN NUTS AND BOLTS:** Apply liberally to frozen nuts and bolts, hinges and sliding and rotating parts. Allow to penetrate into threads. Work parts back and forth, then re-apply to leave a never-dry protective lubricating film. **TO ENSURE ADEQUATE PROTECTION REAPPLY PERIODICALLY.**

PRODUCT SPECIFICATIONS

APPEARANCE	Brown liquid
ODOR	Solvent
FLASH POINT(CONC)	>200° F (T.O.C.)
FLAMMABILITY	Non-flammable spray
VAPOR PRESSURE	68 psig @72 °F
SPECIFIC GRAVITY	0.84
WATER SOLUBILITY	Negligible
SHELF LIFE	> 2 Years in adequate environment
PACKAGING	12 oz. Aerosol Cans 12x1 Case

SAFETY INFORMATION

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

CAUTION: Avoid contact with eyes or prolonged contact with skin.

FIRST AID

SKIN: Wash with soap and water. If irritation develops, seek medical attention. **EYES:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting eyelids occasionally. If irritation persists, seek medical attention. **INGESTION:** Do not induce vomiting. Seek medical attention immediately. **INHALATION:** Remove person to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. Store in a cool, dry place away from heat or open flame. Do not store at temperatures above 120 °F.

HMIS RATING
 0 -Minimal 1-Slight
 2-Moderate 3-Serious
 4-Extreme

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PROTECTION	B



1835 N.E. 144th Street, North Miami, Florida 33181
 (305) 944-2837 • (888) 355-5540 • Fax (305) 944-6857
www.QualityChemical.com